



Wärmeleistung

Heizkörper lackiert							
Bauhöhe mm	Baulänge mm	Bautiefe mm	Heizkörperex- ponent n	Wärmeleistung Watt			
				E-Set Zuordnung Wattleistung	75/65-20 °C	70/55-20 °C 55/45-20 °C	70/55-24 °C 55/45-24 °C
804	450	35	1,2325	400	348	282 184	249 154
804	524	35	1,2275	400	399	324 212	286 177
804	599	35	1,2225	400	451	367 240	324 201
804	749	35	1,2124	600	551	449 294	397 247
804	899	35	1,2023	600	650	530 349	469 293
1172	450	35	1,2321	600	511	415 270	366 226
1172	524	35	1,2271	600	586	476 311	420 260
1172	599	35	1,2221	600	662	538 352	475 294
1172	749	35	1,2120	800	810	659 433	583 363
1172	899	35	1,2020	800	955	779 513	690 430
1448	450	35	1,2318	600	631	512 334	452 279
1448	524	35	1,2268	800	724	588 384	519 321
1448	599	35	1,2218	800	817	664 434	587 363
1448	749	35	1,2118	800	1000	814 535	720 448
1448	899	35	1,2017	1200	1179	962 634	851 531
1770	450	35	1,2256	800	767	623 407	550 340
1770	524	35	1,2206	800	880	715 468	632 392
1770	599	35	1,2155	800	993	808 530	714 444
1770	749	35	1,2054	1200	1216	991 652	877 547
1770	899	35	1,1953	1500	1433	1170 773	1037 649

